




SPECIFICATION

| ITEM | SP-3000 |
|--------------------------|--|
| OUTPUT POWER | CONTINUOUS POWER 3000W SURGE POWER 6000W |
| STANDBY CURRENT | DC 12V < 0.7A DC 24V < 0.5A |
| INPUT VOLTAGE | DC12V : 10V~15V DC24V : 20V~30V |
| OUTPUT VOLTAGE | AC 100V, 110V, 120V, 220V, 230V, 240V |
| OUTPUT WAVEFORM | Modified Sine Wave  |
| EFFICIENCY | > 85% |
| ※ INITIAL CHECKING | AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V |
| ※ OUTPUT REGULATION | ± 5% INTELLIGENT PWM |
| ※ OUTPUT FREQUENCY | 50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED. |
| ※ COOLING | AUTO-OPERATION FAN |
| ※ OUTPUT SHORT | OUTPUT SHORT CIRCUIT PROTECTION |
| ※ LOW BATTERY | < 10.5V or 21.5V ± 0.5V PRE-ALARM < 9.5V or 20V ± 0.5V SHUT DOWN & ALARM |
| ※ OVER HEATING | > 60°C PRE-ALARM > 65°C SHUT DOWN & ALARM |
| ※ OVER LOAD | > 3000W PRE-ALARM > 3200W SHUT DOWN & ALARM |
| BATTERY POLARITY REVERSE | BY FUSE |
| FUSE | DC 12V : 30A * 16PCS DC 24V : 15A * 16PCS |
| AC OUTLET | 2 AC OUTLETS -UK TYPE |
| DIMENSION (L*W*H) | 360*169*152mm |
| NET WEIGHT | 6.9Kg |

※ MARK ARE OUR UNIQUE FUNCTIONS

